



## **CHANCE** project

(Contract Number: 755371)

## TOPICAL DAY ON WASTE CHARACTERIZATION

## DELIVERABLE (D6.4) Work Package 6

Author(s): **C.Bruggeman (SCK•CEN)** 

Reporting period 2: 01/12/2018 – 30/05/2020

Date of issue of this report: 20/05/2019

Start date of project: 01/06/2017 Duration: 48 Months

This project has received funding from the Euratom research and training programme 2014-2018				
under grant agreement No 755371;				
Dissemination Level				
PU	Public	X		
CO	Confidential, only for partners of the CHANCE project and EC			



**D6.4** Topical day on waste characterization Written: C.Bruggeman

Organisation: SCK•CEN Version: 1
Issued: 20/05/2019 Page(s): 2

History chart				
Status	Type of revision	Partner	Date	
Draft	Initial version	SCK•CEN	20/05/2019	

Reviewed by

Approved by

The Executive Board

Safe interim storage and final disposal of radioactive waste (RW) requires effective characterization and quality control of the waste. The CHANCE project therefore aims to address the specific and complex issue of the characterization of conditioned radioactive waste (CRW) by means of non-destructive analytical (NDA) techniques and methodologies. Characterization issues within CHANCE encompass both physico-chemical characterization and radiological characterization.

The CHANCE project will establish a comprehensive understanding of current characterization methods and quality control schemes for conditioned radioactive waste in Europe. Furthermore, CHANCE will develop, test and validate already-identified and novel techniques that will undoubtedly improve the characterization of CRW. These techniques include:

- Calorimetry as an innovative non-destructive technique to reduce uncertainties on the inventory of radionuclides;
- Muon Tomography to address the specific issue of non-destructive control of the content of large volume nuclear waste;
- Cavity Ring-Down Spectroscopy (CRDS) as an innovative technique to characterize outgassing of radioactive waste.

During the CHANCE Topical Day current needs, scientific evolutions and CHANCE highlights concerning conditioned waste characterization using non-destructive techniques were highlighted. The Topical Day took place on Thursday, March 21<sup>st</sup> 2019 at the Lamot Conference Center in Mechelen (Belgium) and was organised by the SCK•CEN Academy. The selected speakers have either operational experience with conditioned waste characterization, or are scientists working on new characterization techniques. This Topical Day therefore also aimed at bringing together these two groups of stakeholders. The book of abstracts of the Topical Day is presented in annex.

The Topical Day gathered a lot of interest from both research, industry, waste management organisations, waste facility operators and institutional/governmental bodies. A total of 102 persons participated to the Topical Day at the Lamot Conference Center. Apart from that, the Topical Day was also live-streamed. A total of 141 different devices logged onto the live-stream during the day, with a maximum peak audience of 42 different devices in the morning session and 33 devices in the afternoon session.

All the Topical Day participants afterwards received a link through email to the different transactions (encrypted pdf files). The video files from the live-streaming are also available upon request.

On Friday morning, March 22<sup>nd</sup>, a visit to the CILVA installation and AQ2 gammaspectrometry installation of Belgoprocess (Dessel, Belgium) was organised. Belgoprocess is the nuclear operator responsible for treating, converting into a stable end product, and storing the historical and current Belgian nuclear waste from numerous producers at its site in Dessel. The company has experience processing almost every type of low-, medium- and high-level radioactive waste at its sites, thereby covering a large segment of the back-end of the nuclear fuel cycle. Such processes lead inevitably to the generation of a number of different waste streams. Each of these streams is uniquely defined by its radiological and physicochemical characteristics. To select appropriate processing and conditioning techniques and disposal options, it is essential to characterize, sample and measure each of these waste streams in an economical manner while meeting all safety, operational and regulatory requirements.

During the technical tour, participants visited the following installations/

- CILVA-installation for overall treatment and conditioning of low-level waste, consisting of the following modules:
  - low-level waste incinerator;



- supercompactor;
- cementation unit;
- cutting and repackaging unit (inl. visual inspections, sampling, ...)
- AQ²-installation (NDA segmented gammaspectrometry) for characterization of low-level waste (and free release).







## Topical Day CHANCE | characterisation of conditioned radioactive waste: status, challenges and new developments March 21, 2019 | Lamot conference centre, Mechelen, Belgium

## Preliminary programme

08:30 – 09:00 h	Registration and welcome coffee
Opening	
09:00 – 09:10 h	Welcome
	Hildegarde Vandenhove, Institute Manager Environment, Health & Safety, SCK•CEN, Belgium
09:10 – 09:30 h	Introduction to the CHANCE project
	Denise Ricard, ANDRA, France – CHANCE coordinator
Chair: Christophe	e BRUGGEMAN, SCK•CEN, Belgium
09:30 – 10:00 h	Radioactive waste characterization practices and gaps in Europe
	Crina Bucur, Raten, Romania
10:00 – 10:30 h	Waste characterisation in practice – lessons learned from operational experience
	Robin Tuerlinckx, Belgoprocess, Belgium & Tomas Vandoorne, NIRAS/ONDRAF, Belgium
10:30 – 11:00 h	Break
11:00 – 11:30 h	Wash and the same and the same in the same and the same a
11:00 – 11:30 h	Waste acceptance and characterization in an operational waste disposal facility
	John Muller, ANDRA, France
11:30 – 12:00 h	Waste characterisation of conditioned waste in Sweden
	Claes Johansson, SKB, Sweden
12:00 – 12:30 h	Recent developments in calorimetry for nuclear wastes characterization
	Christophe Mathonat, KEP Technologies, France
12:30 – 13:45 h	Lunch + poster boards for CHANCE PhD students



## Chair: Denise RICARD, ANDRA, France

13:45 – 14:15 h	Muon tomography   needs and challenges from a safeguards perspective
	Darius Ancius, EC Euratom and Paolo Checchia, INFN, Italy
14:15 – 14:45 h	Muon tomography   recent developments and CHANCE
	Jaap Velthuis, University of Bristol, UK
14:45 – 15:15 h	LINAC-based high energy X-ray imaging of radioactive waste packages at CEA, DEN, Cadarache
	Bertrand Pérot, CEA, France
15:15 – 15:45 h	Break
15.15 15.45 11	Diedk
15:45 – 16:15 h	Novel optical methods for the characterisation of outgassing from radioactive waste
	Guillaume Genoud, VTT, Finland
16:15 – 16:45 h	Modelling of the CHANCE calorimeter and some general thoughts about NDA uncertainty quantification
	Wojciech Kubinski, WUT, Poland and Bart Rogiers, SCK•CEN, Belgium
16:45 – 17:00 h	Closing
	Denise Ricard, ANDRA, France
17:00 – 19:00 h	Reception














## Book of abstracts

# Topical Day CHANCE | Characterisation of conditioned radioactive waste: status, challenges and new developments

March 21, 2019

SCK•CEN
Boeretang 200
BE-2400 MOL
Belgium
www.sckcen.be
academy@sckcen.be



## Book of abstracts

SCK•CEN-32770025 SCK•CEN-BA-118

## Topical Day CHANCE | Characterisation of conditioned radioactive waste: status, challenges and new developments

March 21, 2019

Contact

Dr Michèle Coeck
Head of the SCK•CEN Academy for Nuclear Science and Technology
Boeretang 200
BE-2400 MOL
T +32 14 33 21 80
mcoeck@sckcen.be

## Organising committee

Dr. Christophe Bruggeman (Deputy Institute Manager Environment, Health and Safety (EHS)

Dr. Michèle Coeck (Head of the SCK•CEN Academy for Nuclear Science and Technology, SCK•CEN, Belgium)

Ms Griet Vanderperren (Liaison officer of the SCK•CEN Academy for Nuclear Science and Technology, SCK•CEN, Belgium)

Ms. Monique Van Geel (Administrative and Logistics Support, SCK•CEN, Belgium)

© SCK•CEN Studiecentrum voor Kernenergie Centre d'Etude de l'Energie Nucléaire Boeretang 200 BE-2400 MOL Belgium

www.sckcen.be

Status: Unclassified

## RESTRICTED

All property rights and copyright are reserved. Any communication or reproduction of this document, and any communication or use of its content without explicit authorization is prohibited. Any infringement to this rule is illegal and entitles to claim damages from the infringer, without prejudice to any other right e.g. in case of granting a patent or registration in the field of intellectual property. This document is distributed to a limited list of invited and involved people. The content is a general abstract or paper and does not jeopardize the novelty of underlying inventions. Copyright of the individual abstracts and papers rests with the authors and the SCK•CEN takes no responsibility on behalf of their content and their further use.

SCK•CEN, Studiecentrum voor Kernenergie/Centre d'Etude de l'Energie Nucléaire Stichting van Openbaar Nut – Fondation d'Utilité Publique - Foundation of Public Utility Registered Office: Avenue Herrmann Debroux 40 – BE-1160 BRUSSEL

Operational Office: Boeretang 200 – BE-2400 MOL

## Introduction to the CHANCE project

Denise Ricard ANDRA, Châtenay-Malabry, France

denise.ricard@andra.fr

## Abstract

Context and objectives of the project

The CHANCE project aims to address the specific issue of the characterization of conditioned radioactive waste (CRW). The characterization of fully or partly conditioned radioactive waste is a specific issue because, unlike for raw waste, its characterization is more complex and needs specific non-destructive techniques and methodologies. There are different and varying reasons for this: 1) conditioned waste may no longer be in its initial form (e.g., due to incineration), 2) conditioned waste is typically embedded or surrounded by a matrix, 3) conditioned waste may contain wastes coming from different primary sources and therefore the radiological spectrum might become more complex.

CHANCE will focus on conditioned waste of the following activity levels:

- Very Low Level Waste (VLLW);
- Low Level Waste (LLW);
- Intermediate Level Waste (ILW);
- High Level Waste (HLW).

The first objective of CHANCE is to establish at the European level a comprehensive understanding of current conditioned radioactive waste characterization and quality control schemes across the variety of different national radioactive waste management programmes, based on inputs from end-users such as Waste Management Organizations and storage operators.

The second objective of CHANCE is to further develop, test and validate techniques already identified that will improve the characterization of conditioned radioactive waste, namely those that cannot easily be dealt with using conventional methods.

To address these specific issues, the CHANCE project proposes R&D actions to develop three innovative technologies for conditioned radioactive waste packages, namely:

- Calorimetry as an innovative non-destructive technique to reduce uncertainties on the inventory of radionuclides;
- Muon Tomography to address the specific issue of non-destructive control of the content of large volume nuclear waste;
- Cavity Ring-Down Spectroscopy (CRDS) as an innovative technique to characterize outgassing of radioactive waste.

The activities performed and the results obtained within the project CHANCE are integrated, communicated and disseminated both between the project partners as well as with the broader European community involved in radioactive waste disposal. Dissemination of results and progress is an integral part of the CHANCE project. Generally stated, the goal of communication is to raise awareness concerning the CHANCE research topics and developments, and to inform the CHANCE stakeholders about the project's progress and achievements. The main communication tool to reach this goal is CHANCE website http://www.chance-h2020.eu/.

The final ambition of CHANCE is to improve the efficiency of the characterization of conditioned radioactive waste and therefore to improve the safety of the global radioactive waste management process throughout the full storage cycle, including transport, interim storage and final disposal operational and long term stability.

## Project Overview

CHANCE is structured into six work packages:

- Management and coordination (WP1)
- Methodology for conditioned radioactive waste characterization: Problematic wastes and R&D proposal (WP2)
- Calorimetry associated with non-destructive assay techniques and uncertainties study (WP3)
- Muon imaging for innovative tomography of large volume and heterogeneous cemented waste packages (WP4)
- Innovative gas and outgassing analysis and monitoring (WP5)
- Dissemination activities (WP6)

WP1 is dedicated to the management and coordination of the project.

WP2 is dedicated to the establishment at the European level of a comprehensive understanding of current conditioned radioactive waste characterization and quality control schemes across the variety of different national radioactive waste management programmes, based on inputs from end-users such as Waste Management Organisations and storage operators.

WP3 objective is to complement existing, widely-used techniques for characterization of waste packages (gamma spectrometry and passive neutron measurement) with an exhaustive study of uncertainties related to such characterization methods in conjunction with calorimetry.

WP4 objective is to develop mobile muon tomography instrumentation to address the as-yet unsolved problem of the non-destructive assay (NDA) of large volume nuclear waste packages, such as large spent fuel casks and large concrete waste packages with heterogeneous waste.

WP5 will advance the use of Cavity Ring-Down Spectroscopy (CRDS) as an innovative technique to characterize outgassing of radioactive waste by developing new instrumentation for H<sup>36</sup>Cl and demonstrating an application of the technique to the monitoring of radiocarbon outgassing.

WP6 is dedicated to dissemination and training activities.

Acknowledgment "This project has received funding from the Euratom research and training programme 2014-2018 under grant agreement No 755371".		

## Radioactive waste characterisation: practices and gaps in Europe

Crina Bucur Institute for Nuclear Research (RATEN ICN), Pitesti, Romania

crina.bucur@nuclear.ro

### Abstract

The CHANCE project "Characterization of conditioned nuclear waste for its safe disposal in Europe" aims to address the specific issue of the characterization of conditioned radioactive waste in Europe. A questionnaire was elaborated by CHANCE Work Package 2 & 6 to obtain a broad overview on the end-users needs for the characterisation of conditioned radioactive waste and to appreciate how the members of End User Group (EUG) perceive the activity of waste characterization in relationship with the evolution of the national disposal programme, in terms of importance with respect to the whole back-end of the fuel cycle, or in terms of uncertainty management within each organization.

The answers collected from the CHANCE EUG members were used to identify:

- key parameters that need characterization;
- technologies/methods commonly used for characterization of conditioned waste;
- waste acceptance criteria applied and the possibilities of their harmonization in Europe
- specific problematic issues for the characterization of conditioned radioactive waste;
- R&D needs and potential on-going R&D programme on the topic of conditioned radioactive waste characterization;
- potential applications of R&D actions to be included in CHANCE;
- socio-technical and ethical issued associated with the waste characterization process

The methods used for characterisation of conditioned radioactive waste depend on the country approach. Spectroscopic techniques (alpha, beta and gamma) as well as neutron measurements and dose rate calculation are used in most European countries, but in some organizations, more advanced techniques such as muon tomography and Calorimetry are also applied in the characterisation process.

Despite the use of various conditioning technologies and matrices, there are common difficulties related to the characterization process of the conditioned waste packages. Characterization of the conditioned historical waste packages seems to represent a generalized problem. Radiologic characterisation of these waste packages represents a big challenge either with passive or active measurements because of the difficulty of the interrogators radiation to penetrate the waste matrix and of the strong attenuation of the measurable emissions (gamma or neutron) by the waste package itself.

## Waste characterization in relation to the WAC: approach and challenges ahead

Robin Tuerlinckx, Belgoprocess NV, Dessel, Belgium Tomas Vandoorne, NIRAS/ONDRAF, Brussels, Belgium

robin.tuerlinckx@belgoprocess.be t.vandoorne@nirond.be

### Abstract

In Belgium, ONDRAF/NIRAS (National Agency for Radioactive Waste and Enriched Fissile Materials) is responsible for the long-term management of radioactive waste. Belgoprocess, as the industrial subsidiary of ONDRAF/NIRAS, is entrusted with the operational waste management. A very important aspect in this overall strategy are the waste acceptance criteria (WAC) and the characterization which is eventually performed in the assessment of these WAC.

Currently ONDRAF/NIRAS is in the final stages of obtaining the license for the near surface disposal site (cAt), which is expected to be operational in 2024. During the last years, a lot of effort has been made considering the final set of WAC. These final WAC have a great impact in the way characterization is to be performed, considering both radiological and chemical content. Some challenges were identified to tackle this need for detailed (extra) characterization information.

This presentation gives an overview of these criteria and the way that these needs can be fulfilled in the overall characterization program. Another important aspect is the control strategy, based on qualification and a control mechanism.

## Waste acceptance and characterization in an operational waste disposal facility

John Muller, Denise Ricard ANDRA, Châtenay-Malabry, France

john.muller@andra.fr

## **Abstract**

The Centre de Stockage de l'Aube (CSA) is a basic nuclear installation designed to dispose Low and Intermediate Level Waste Short-Lived Waste (LILW-SL). The industrial operating of CSA started in 1992 and it is planned to operate this disposal facility for about 70 years (the operating period will be followed by a 300-year monitoring phase). The disposal capacity of the CSA is 1 000 000 m<sup>3</sup> which will correspond approximately to the filling of 400 disposal vaults (today about 140 vaults are filled).

## Waste acceptance processes

The overall structure of the waste acceptance process includes the following phases:

- Approval (of a waste stream);
- Authorization (of a site, for the approved waste stream);
- Acceptance (of a waste production of an approved waste stream produced on an authorized site). A document, called Compliance Matrix (MC) is gradually filled up during the process, and each stage of completion of the document is associated with a phase of the acceptance process.

Once the initial approval and acceptance delivered by Andra, the waste producer must define and perform a surveillance program to identify all the risks during the production of waste packages that could lead to produce and ship waste packages non-compliant with waste acceptance criteria of Andra. The surveillance process is defined and validated during the approval process.

Andra, as a part of the requirements of its license to operate the Low and Intermediate Level Waste Short-Lived Waste (LILW-SL) facility, verifies that the waste producers' capability to produce waste packages are compliant with the approval and authorizations delivered.

The surveillance program includes:

- Destructive control on waste packages at the waste producer's site and at the CSA after delivery;
- Non-destructive control on waste packages at the waste producer's site and at the CSA after delivery;
- Surveillance missions at the waste producer's site;
- Controls on the waste package information sent prior to delivery at the CSA;
- Controls performed upon delivery at the CSA (visual, radiological controls...).

## Monitoring of waste package quality by Andra

Surveillance is a mission assigned by the terms of the disposal facility-operating license. Andra must periodically verify the actual and correct application by the producer of the technical and organizational conditions on which the authorization was notified. For this purpose and in addition to computerized verification checks and checks carried out at the reception of waste package at the CSA, Andra must carries out in its Annual Monitoring Program, which includes:

• Destructive and non-destructive testing of packages carried out on delivery to the CSA. Destructive and non-destructive sampling checks are performed by Andra or contracted laboratories under the responsibility of Andra to ensure the compliance of the package (container, packaging, conditioning, chemical and physical nature of waste, evaluation of activity...).

These controls are planned by Andra as part of the implementation of its Annual Monitoring Program. During these checks, Andra can detect non-compliances but also slightly abnormal situations (also called weak signals), which, although compliant, will trigger the attention of Andra

Surveillance missions at the production facilities. Andra carries out surveillance missions at the production sites to ensure the effective and correct application by the producer of the technical and organizational conditions on the basis of which approval and authorization have been notified. These missions can take the form of process audit, technical visits and participation in internal surveillance activities.

This monitoring is based on a 3 years planned quality-control inspections (destructive or non-destructive):

- To sample and control waste packages received at CSA integrating:
  - A minimal 3 years period for each package family;
  - A systematic control for new agreements and new delivery of suspended agreements;
  - Experience feedback from quality control.
- To check the consistency between results and declared properties for measurable parameters;
- To ensure of the compliance of corresponding parameters with specifications;
- To acquire knowledge.

These quality control inspections applies the same rules and methods as those defined in the specifications, technical tests and standards.

## Focus on non-destructive controls

Non-destructive tests carried out on the packages delivered to the CSA aim at carrying out the verification of the characteristics of the waste packages declared by the producer by comparing them with the values measured by Andra and those contained in the acceptance folder.

In addition to a detailed review of the package file sent by the producer, non-destructive controls include visual and radiological controls (non-surface contamination and dose equivalent rate mapping), weighing and dimensional readings for all waste packages collected are performed. Gamma spectrometry measurements are also carry out for a large majority of waste packages (only cubic containers of 5 and 10 m<sup>3</sup> to be inject at the CSA are not measured in gamma spectrometry).

These controls, carried out on the CSA, can be supplemented by non-destructive tests carried out by external laboratories. These controls consist mainly of high-energy X-ray imaging (radiography and tomography), low-energy x-rays, but also passive and active neutron measurements coupled with gamma spectrometry measurements.

Depending on the nature of waste package, additional controls can be done to verify the internal characteristics of the packages (integrity, quality of the waste block, internal constitution of the packages) and also to reinforce the results of the activity measurements carried out at the CSA with others methods.

## Note

1.

In the near future, Andra will have a facility (called package control facility) on the CSA that will be able to perform on drums:

• Tritium and carbon 14 degassing measurements; High energy X-ray imaging

## Waste characterisation of conditioned waste in Sweden

Claes Johannsson Swedish Nuclear fuel and Waste Management (SKB), Solna, Sweden

claes.johansson@skb.se

### **Abstract**

Nuclear facilities and installations in Sweden consist of both nuclear power plants in operation (8) and plants (4) under decommissioning. In the next coming years two more NPP:s will be shut down.

SKB – Swedish Nuclear fuel and Waste Management was established of the owners of the NPP:s to take care of both the spent fuel after operation and the low and intermediate level waste from the NPP:s and also from the Studsvik nuclear site and some other producers in Sweden of radioactive waste.

Since 1988 SKB have a final repository SFR in operation at Forsmark that takes care of mainly short lived radioactive waste. Limitations due to the existing licence for receiving activity are 10E16 Bq in total. Most of the waste is transported by a special designed ship for radioactive waste from the nuclear facilities to SFR.

For the SFR facility there are existing waste acceptance criteria that must be fulfilled to be able to dispose of the waste. The waste is either examined before conditioning of the waste and/or after it is conditioned.

The normal waste characterisation methods for examining the conditioned waste consist of gamma dose rate measurements and gamma spectrometry measurements of the waste packages. The waste packages could be of different kind of geometries.

For old legacy waste that exist with very poor waste characterisation done, a special project has been performed at SKB:s sister company SVAFO at the Studsvik site. At this project (X-ray project) about 7000 drums was examined with x-ray examination in order to identify liquids, and other type of waste in this drums. At the same time also gamma specific measurements where performed as a quick scan for about 15 minutes each of the drums.

## Recent developments in calorimetry for nuclear wastes characterization

Christophe Mathonat KEP Nuclear, Caluire et Cuire, France

christophe.mathonat@kep-technologies.com

### Abstract

Calorimetry is a non-destructive method of quantitative measuring the heat emission to determine the masses or activities of nuclear material hidden inside nuclear waste compounds. Heat-flow calorimeters are in common use for measuring thermal powers over a wide range of 0.5mW (equivalent to 0.2g of low-burnup plutonium) up to 1kW and for samples of various sizes of about a few cm³ up to large waste drums of 60cm wide and 100cm long 0.

Calorimetry is measuring the overall thermal power due to the radioactive decay coming from the waste contained in a metallic drum or a different container. It has many advantages as it features a non-destructive method which remains independent of matrix effect or the chemical composition.

For measuring a multi-nuclide drum calorimetric assay is often combined with gamma ray and neutron measurements. Calorimetric determination of tritium and plutonium activities or masses has become common practice. However, the determination of beta-emitters (e.g. Sr/Y-90) or shielded sources inside a concrete filled waste compound is yet challenging for the comprehensive nuclide characterization of large heterogeneous waste drums.

In the context of the CHANCE work-package 3 0, 0, a benchmark of calorimeters and standard NDA methods for the characterization of large volume waste drums 0 have been undertaken and a study of the neutron and gamma ray signals that can escape various 200L waste drum matrices with different source configurations has been performed. A 200 liters calorimeter is under construction with an optimized detection limit and to reduce the methodological uncertainties of the inventory determination in a multi-nuclide matrix, the escaping radiation are quantized as much as the encapsulated gamma-rays and  $\alpha$ -,  $\beta$ -, n- particles depositing radiological heat inside the drum. Monte Carlo simulations are utilized resembling the waste drum and the calorimeter in both, their geometries as well as the material compositions. For the analyses, the particle flux and energy deposition in each layer of the calorimeter are displayed. The results yield that a significant part of the emitted radiation leaves the system and does not contribute to the heat deposited inside the drum. Therefore additional layers of gamma and neutron absorber are contemplated and associated numerical studies are initiated.

## References

- [1] D.S. Bracken, C.R. Rudy, Principles and applications of calorimetric assay, LA-UR-07-5226
- [2] D.S. Bracken, R.S. Biddle et. al., Application Guide to Safeguards Calorimetry, LA-13867-M, January 2002
- [3] D. Ricard, S., Plumeri, L.Boucher, A. Rizzo, H. Tietze-Jaensch, C. Mathonat, C. Bruggeman, J. Velthuis, L Thompson, G. Genoud, C. Bucur, D. Kikola, G. Zakrzewska-

- Koltuniewicz, (2018). The CHANCE project "Characterization of conditioned nuclear waste for its safe disposal in Europe". DEM 2018 - Dismantling Challenges: Industrial Reality, Prospects and Feedback Experience, France, Avignon – 2018, October 22 – 24
- [4] CHANCE 2020: http://chance-h2020.eu
- CHANCE delivery report D3.1 published on <a href="http://chance-h2020.eu">http://chance-h2020.eu</a> [4]; W. R. Kubinski, [5] MSc. Thesis, Faculty of Physics, Warsaw Univ. of Technology, Sep. 2018

## Muon tomography: needs and challenges from safeguards perspectives

Daruis Ancius, EC Euratom, Brussels, Belgium Paolo Checchia, INFN, Legnaro, Italy

<u>Darius.ANCIUS@ec.europa.eu</u> checchia@padova.infn.it

### **Abstract**

European Union strategies related to Energy Union and Energy Security underline the importance of highest standards of safety, security, waste management and non-proliferation. It implies obligations for safe and responsible long-term spent fuel and waste management.

Raising number of spent fuel assembly loadings to Dry Storage Containers (DSC), the construction of new type facilities like Encapsulation plants and Geological repositories becomes serious challenge for EURATOM and IAEA. The proven traditional approaches based on maintenance of Continuity of Knowledge (CoK) of safeguarded materials are relying on continuous video surveillance and sealing. It requires considerable human resources. Moreover, given the big number of DSC (some thousands in EU in next decade) and interim storage for about 50 years, the cases with the loss of CoK are highly probable. Such cases would necessitate the verification that all spent fuel assemblies are present in DSC. However today no NDA technique can prove it and only way to confirm this is to unload the DSC in a water pool or a hot cell.

Cosmic muons penetrate metres of dense material and therefore can be used to image the contents of spent fuel held in DSC. Recent development of innovative imaging techniques using cosmic muons and muon trackers offers unique opportunities for safeguards. The National Institute of Nuclear Physics (INFN) in Italy and EURATOM tested the 8 x 8 drift-tube detector at proximity of CASTOR® container in Germany. The tests have convincingly proved that the detection of the muons that passed through the container is possible. The noise created by gamma and neutron radiation from spent fuel stored in this container represented only about 1% of useful signal. These experimental results justify other investigations related to the use of the muon trackers for spent fuel safeguards. Further tests with larger scale muon trackers are under consideration.

**Keywords** 

Safeguards, muon detection, spent fuel, CASTOR.

# Muon imaging for innovative tomography of large volume and heterogeneous cemented waste packages

Jaap Velthuis University of Bristol, Bristol, United Kingdom

jaap.velthuis@bris.ac.uk

## **Abstract**

A mobile muon tomography system is being commissioned in a non-laboratory environment to address the as-yet unsolved problem of the non-destructive assay of large volume nuclear waste packages, such as large spent fuel casks and large concrete waste packages with heterogeneous waste.

Muons are natural occurring particles with a flux at ground level of around 1 cm<sup>-2</sup>min<sup>-1</sup>; they are capable of passing through several hundred metres of rock. When they interact with matter, they scatter depending on the atomic number, Z, of the material. Hence, if muon trajectories are measured before and after traversing a volume, an image of the different materials in that volume can be produced. This mature and well-established technique is known as 'muon tomography' (MT). It has been successfully utilised in e.g. cargo screening for nuclear contraband. MT is fully passive and works for heavily-shielded volumes; it is also highly complementary to gamma and neutron tomography. The technique is particularly useful to detect heavy elements like lanthanides and actinides, but can also be applied to detect light elements and gas bubbles and density gradients or differences within a matrix.

The system is in an advanced stage of commissioning. Combining the knowledge and experience gained operating prototype systems and details and realistic Monte Carlo simulation program is well underway. A large Monte Carlo effort is well underway. The work includes comparison studies of the performance of different reconstruction algorithms to determine the contents of the waste drums focusing both of high-Z materials and gas bubbles. This has led to the development of a unique approach using figures of merit to enable performance comparisons between different algorithms and/or instrumentation techniques. For example, we have shown that we can resolve the presence of a uranium target object down to 4mm using our system in a concrete drum, can detect gas bubbles with a volume over 1L in concrete, discriminate between Pb, W and U, measure the size of objects with mm precision and study the minimum spacing between two objects to see them separately.

## LINAC-based high energy X-ray imaging of radioactive waste packages at CEA

Bertrand Pérot Nuclear Measurement Laboratory, CEA, DEN, Cadarache, France

bertrand.perot@cea.fr

## **Abstract**

In order to inspect the interior of a waste package without having to carry out a destructive action, high-energy photon imaging technique (radiography and tomography) can be used in the manner of a medical scanner. The package to be inspected is placed between the photon source and the detector. The image delivered by the detector reports the absorption of photons through the object. The thicker and denser the object, the greater the absorption. In order to image large and dense radioactive waste packages, such as 2 m3 concrete drums with a diameter of more than 100 cm, a high intensity and high energy X-ray source based on an electron linear accelerator (LINAC) has been implemented in CINPHONIE facility, at CEA DEN Cadarache. Our current "Mini-Linatron" LINAC produces 9 MeV electrons that collides a tungsten target, producing a Bremsstrahlung photon beam with a dose rate close to 20 Gy.min-1 at a distance of 1 m from the target, in the axis of the beam. Radiographic and tomographic images are produced with a millimeter resolution, allowing precise visualization of the interior of waste packages (pictures of the linear attenuation coefficient in each pixel, which can be converted to density through hypothesis on the nature of materials). A new "SATURNE" LINAC with an electron energy up to 20 MeV and a dose rate larger than 100 Gy.min-1 at 1m is currently being commissioned in CINPHONIE, which will allow imaging objects up to 150 cm of concrete or 40 cm of iron thick.

The use of such high-energy photons requires specific detectors and CINPHONIE is currently equipped with two acquisition systems. The first detector is a 2D wide-field screen of  $80\times60~\text{cm}^2$  with a "Gadox" (Gd2O2S) scintillator coating for rapid imaging but with limited attenuation dynamics of about 3 decades, corresponding to 100 cm of concrete or 25 cm of steel. The second system is a fan array of 25 CdTe semiconductor bar detectors, with collimators oriented towards the focal spot of the photon beam, for quantitative computed tomography with attenuation dynamics of approximately 5 decades, i.e. 1.5 m of concrete or 40 cm of steel. New scintillator screens for large field of view detection are being tested in our laboratory, as well as large and continuous linear detectors (CdWO4 needles or flat CsI scintillators with on-edge X-ray beam) to avoid the horizontal sweeping scan of the package imposed by gaps between the collimated CdTe, and thus to reduce acquisition time. Recent tests of ModuPIX detector, which will equip the underwater X-ray imaging system of the future experimental Jules Horowitz Reactor, will also be reported. This detector based on TimePix chip (CERN) coupled with very thin cadmium telluride or silicon semiconductors with on-edge beam irradiation should allow reaching a very good spatial resolution (close to 100  $\mu$ m).

Finally, we will report ongoing R&D studies aiming at determining the mean effective atomic number of materials in radioactive waste packages. The principle is based on performing acquisitions at different X-ray energies to take advantage of the differences in attenuation according to photon beam energy and atomic number of the elements. This method applied on computed tomography allows extracting both the density and the effective atomic number from the attenuation information, and thus refines the identification of materials. We will also mention the development of TOMIS, a transportable tomographic system to perform in situ imaging of large concrete waste packages, involving dual energy computed tomography as well.

## Novel optical methods for the characterisation of outgassing from radioactive waste

Guillaume Genoud VTT, Espoo, Finland

Guillaume.Genoud@vtt.fi

## **Abstract**

Long-lived radionuclides are particularly challenging to detect in the context of nuclear facilities. They are the main source of radioactive gas emissions and must therefore be monitored. Radiocarbon is for example produced in all part of nuclear power plants and can then be released in the form of carbon dioxide or methane through the biodegration of radioactive waste. Long-lived radionuclide in general, such as radiocarbon and tritium, are problematic because they have a high residence time in the environment and can easily be assimilated into living matter. A proper management of nuclear wastes containing these nuclides is necessary due to their potential impact on human health and the environment. They are highly mobile in the environment [2], and must be monitored for long-time, because of their long half-life. In the context of conditioned nuclear waste, characterisation of the waste outgassing is necessary. Gaseous emissions from radioactive waste usually mostly consist of tritium and radiocarbon, mainly emitted in the form of water vapour (HTO), carbon dioxide (14CO<sub>2</sub>) and methane (14CH<sub>4</sub>). H<sup>36</sup>Cl is also of interest in the particular case of graphite waste.

Unfortunately, there are no method capable of rapid in-situ analysis of those radionuclides. Current methods require samples collection and off-line analysis in the laboratory by liquid scintillation counting (LSC). Scintillation peaks of those radionuclides overlaps in LSC limiting its sensitivity and often requiring time-consuming radiochemistry method to separate the different beta emitters. On the other hand, novel optical methods for detection of long-lived radionuclides from nuclear facilities have been developed in recent years. In particular, cavity ring-down spectroscopy (CRDS) has been shown to provide high sensitivity for radiocarbon and tritium detection in the form of carbon dioxide [3] and water vapour [4], respectively. CRDS is one of the most advanced and sensitive laser spectroscopy technique [5 - 6]. It is an isotopically selective laser spectroscopic technique and provides the highest sensitivity, allowing for the detection of extremely small amounts of radioactive gases, and thus detection of the smallest leaks.

In the CHANCE project, these methods are further developed to determine the outgassing rate of various radioactive molecules. The potential of CRDS for waste package monitoring is

1.

explored, since this technique has not been used in this context before and has several advantages over conventional techniques. The CHANCE project focuses on the detection of radiocarbon and <sup>36</sup>Cl isotopes. CEA is developing a novel instrument for the detection of H<sup>36</sup>Cl based on CRDS. This is the first time that CRDS is used to detect this molecule, which is highly relevant in the case of outgassing from graphite waste. At VTT, an already-developed CRDS instrument for the detection of radiocarbon compounds will be used to study in detail their outgassing rate in various types of waste. The goal is to provide valuable information about the radiocarbon release kinetics and its speciation, including methane and carbon dioxide. Further work, in collaboration with ENEA, will consist of validating the technique and compare it to traditionally used techniques such as LSC. This work will therefore result in a major step forward in the development of the use of optical methods to detect radioactive gas emissions.

## References

- [1] Man-Sung Yim and François Caron, "Life cycle and management of carbon-14 from nuclear power generation", Progress in Nuclear Energy 48, 2 (2006)
- [2] International Atomic Energy Agency, "Management of Waste Containing Tritium and Carbon-14", Technical Reports Series No. 421, IAEA, Vienna (2004).
- [3] G. Genoud, M. Vainio, H. Phillips, J. Dean, and M. Merimaa, "Radiocarbon dioxide detection based on cavity ring-down spectroscopy and a quantum cascade laser", Opt. Lett. 40, 1342 (2015).
- [4] C. Bray, A. Pailloux, and S. Plumeri, "Tritiated water detection in the 2.17 mm spectral region by cavity ring down spectroscopy", Nucl. Instrum. Meth. A 789, 43 (2015).
- [5] D. Romanini, A. Kachanov, N. Sadeghi, and F. Stoeckel, "CW cavity ring down spectroscopy", Chem. Phys. Lett. 264, 316 (1997).
- [6] G. Berden, R. Peeters, and G. Meijer, "Cavity ring-down spectroscopy: experimental schemes and applications", Int. Rev. Phys. Chem. 19, 565 (2000)

## Modelling of the CHANCE calorimeter and some general thoughts about NDA uncertainty quantification

Wojciech Kubinski, Politechnika Warszawska, Warszawa, Poland Bart Rogiers, SCK•CEN, Mol, Belgium

w.r.kubinski@gmail.com bart.rogiers@sckcen.be

### **Abstract**

Calorimetry is one method for the determination of nuclear material masses (or activities) by the quantitative measurement of heat flux, emerging from a sample. Calorimetry is used for non-destructive assay (NDA) which means that no sample needs be tempered with or destroyed by the analysis. Heat-flow calorimeters have been used successively for measuring a wide range of thermal powers i.e. from 0.5 mW (0.2g of low-burnup plutonium) up to 1kW for samples varying in size from about 2.5 cm up to 60 cm wide and 100 cm long [1,2].

The MCNP6-based numerical model of the Large Volume Calorimeter (LVC) designed by KEP Nuclear (France) was set up. Various scenarios were simulated for different particles types, energies and source locations to accompany and support the interpretation of calorimetric KEP-LVC measurements within the CHANCE project [3]. For the analyses, the particle flux and energy deposition in each layer of the calorimeter are plotted. The results yield that a significant part of the gamma and neutron radiation leaves the system and does not contribute to the heat deposited. Moreover, the high-energy part of the gamma and neutron radiation flux can reach the reference chamber of the calorimeter and deposit some energy there, compromising the calibration and causing double-bias.

A particle flux study of the 200L mock-up drum and the KEP-LVC calorimeter will be presented and discussed. A tally 4 with mesh option for both gamma and neutron of up to 5 MeV was used to simulate the mean flux in each cell and for various source location and source distribution patterns. The simulations showed that, depending on source location and power, neutron radiation and high-energy gamma radiation leakage can influence the final heat measurement differently. In general, part of the realized simulations suggest that for some possible scenarios - with samples containing nuclei of high cross sections for  $(\alpha,n)$  and other neutron-producing reactions, high activity beta-emitters (bremsstrahlung radiation) or gamma-emitters - the accuracy of calorimetric assay can be decreased due to radiation escape.

## References

- [1] Principles and applications of calorimetric assay, D.S. Bracken, C.R. Rudy, Los Alamos Report, 2007, LA-UR-07-5226
- [2] Application Guide to Safeguards Calorimetry, D.S. Bracken, R.S. Biddle et. al., Los Alamos Report, 2002, LA-13867-M

Page 29 of 20

Topical Topical Day CHANCE | Characterisation of conditioned radioactive waste: status, challenges and new


- [3] D.Ricard, D., Plumeri, S., Boucher, L., Rizzo, A., Tietze-Jaensch, H., Mathonat, C., Bruggeman, C., Velthuis, J., Thompson, L., Genoud, G., Bucur, C., Kikola, D., Zakrzewska-Koltuniewicz, G. (2018). The CHANCE project "Characterization of conditioned nuclear waste for its safe disposal in Europe". DEM 2018 Dismantling Challenges: Industrial Reality, Prospects and Feedback Experience, France, Avignon 2018, October 22 24; and CHANCE web site: http://chance-h2020.eu
- [4] CHANCE delivery report D3.1 published on http://chance-h2020.eu

## Annex: presentations













## CHANCE

## Introduction to the CHANCE project

enise Ricard, H. Tietze-Jaensch, A. Rizzo, C. mat, C. Bruggeman, J. Velthuis, L. Thompson, G. senoud, C. Bucur, D. Kikola, G. Zakrzewska-Koltuniewicz, O. Guéton

## CHANCE

### Introduction

- CHANCE: "Character
- Funded by Euratom research and training programme 2014-2018 under grant agreement N\* 755371
- Within the NFRP 7-2016-2017 topic "Research and innovation of overall management of radioactive waste other than geological disposal"
- Duration of 4 years; start date June 1, 2017; end date: 31 May, 2021
- Total CHANCE budget 4,25 ME
- EC contribution: 3,98 M€
- Consortium: 12 partners from 8 European countries



## CHANCE

- Andra (FRA)
- CEA (FRA)
- ENEA (ITA) FZJ (GER)
- KEP Nuclear (FRA)
- SCK+CEN (BEL)
- University of Bristol (UK)
- University of Sheffield (UK)
- VTT (FIN)
- RATEN (ROM)
- WUT (POL)
- INCT (POL)



JÜLICH





Consortium









## CHANCE

## CHANCE objectives (1)

- To establish at the European level a comprehensive understanding of current conditioned radioactive waste characterization and quality control schemes across the variety of different national radioactive waste management programment.
  - Based on inputs from end-users such as Waste Management Organisations, regulators, waste producers and repository operators

## CHANCE

## **CHANCE** objectives

- ner develop, test and validate non-destructive uses that will improve the characterization of oned radioactive waste (CRW) and complement ology while particularly targeting large and eneous waste compounds

Destructive technologies followed by chemical or radiological analyses are commonly used techniques for radioactive waste characterization but are not addressed in CHANCE, since these techniques are applied to the raw waste itself, this is not in the scope of this project.


## CHANCE


## CHANCE objectives (3)


- CHANCE will focus on the following waste forms (IAEA classification):
  - ➤ Very Low Level Waste (VLLW)
  - > Low Level Waste (LLW)
    > Intermediate Level Waste (ILW)
    > High Level Waste (HLW)
- Very Short Lived Weste and Exempt Waste are beyond the scope of CHANCE as these kinds of waste are not destined for a specific radioactive waste disposal





1





























## To develop new solutions for the characterization of conditioned radioactive waste to solve specific issues To improve radioactive waste classification To improve the global safety of the whole chain of radioactive waste management To contribute to an European homogenized approach for the characterization of conditioned radioactive waste To improve common practice in terms of conditioned radioactive waste characterization To maintain and enhance knowledge and competences To improve public confidence







## CHANCE

General considerations on radioactive waste characterisation

## CHANCE

### Why characterisation of RW is important?

For producing a "quality end product" for all disposed RW

it could be achievable by obtaining a thorough and accurate assessment of the physical, chemical and radiological characteristics of the waste

According to IAEA recommendations [IAEA-TECDOC-1537], RW characterisation must be:

- accomplished or verified with a clear demonstration of the compliance with WAC for interim storage, transport and final disposal accomplished in a systematic manner using proven methodologies, technologies and techniques with emphasis on quality assurance (QA) and quality control (QC).

Proper control of safety relevant parameters of RW within the entire waste management life cycle, and careful testing of the quality of final waste forms and waste packages, are principal components in any waste management strategy

## CHANCE

## On what is based the characterisation process? (1/2)

The type and extent of the characterization efforts depend on many factors, such as:

- · the type of waste or waste form;
- the disposal concept;
- the regulatory regime;
   the amount of process knowledge that is available;
- . the kind of characteristics to be measured.
  - It is impossible to define or recommend a single characterization procedure for even similar waste forms or packages.


## CHANCE

## On what is based the characterisation process? (2/2)

According to the IAEA recommendations [IAEA-TECDOC-1537], the strategy for the RW characterization should be based on understanding and assessment of the:

- the waste acceptance criteria and the rationale behind it;
- the safety assessment for the disposal concept: assumptions made, information needed ...
- process control and quality assurance requirements, transportation requirements, and worker safety requirements.

Planning for waste characterization should take place in advance of waste generation to ensure that all stages in the waste management are accomplished in a controlled manner.



### CHANCE Techniques/methodologies used in RW characterisation (1/2)

- Process knowledge: knowledge and documentation of the processe that generate RW is an effective way of assessing the RW characteristics
- Non-destructive examination and assay (NDE and NDA):
  - NDE involves checking the physical and mechanical properties of the waste package
  - o NDA involves analysis of the content of one or more RN in waste package without affecting the physical or chemical form of the material. Selection of a specific NDA techniques depend on the radionuclides (y-X ray entites or fissile material) and the relevant parameters of the waste package (type of matrix, radioactivity, sources and density distribution, shape and dimensions of the container and inner/outer shielding)
- Destructive analysis (DA) involves sampling, sample preparation chemical separation methods (radiochemistry) and radiometric determination

# CHANCE Techniques/methodologies used in

- RW characterisation (2/2)
  The measured RNs are categorized in:

  asy to measure (ETM) can be determined by direct measurements (i.e. y-emitters);
- difficult to measure (TTM) cannot be determined by direct measurement in the waste form (i.e. pure-β emitters, low-energy X-ray emitters, a emitters); impossible to measure (TTM) measurement of their activity would require unjustified

The nuclide vector (NV) methodology: qualitative identification of all RNs of specific waste stream

The scaling factor (SF) methodology: determines the activity of DTM and ITN radionuclides using correlations between them and key nuclides (KN) choser among the ETM. SFs are waste stream and case specific

A combination of different techniques (e.g. alpha spectrometry, mass spectrometry and gamma spectrometry) are used together with modeling activities to determin the NVs and SFs. The sample and location for sampling are very important and have to be representative for the waste stream considered.

Nave to be representative.

Using a NDA system, waste packages are measured to determine KN concentration and by using the SFs and NVs the associated DTM, ITM and ETM nuclides are ther calculated and declared for each package.

### CHANCE

### **NDA** methods

Use standards calibration or modelling and could have high uncertainty associated to the activity determined.

- Gamma methods rely on capturing gamma photons emitted from the waste package as result of radioactive decay of the radionuclides present in the waste
- Neutron methods typically rely on capture of neutrons emitted either through spontaneous fission or (q,n) reactions and are primarily used to identify and quantify fissile or fertile isotopes in the waste
   Calorimetry relies on measuring the specific heat generated from radioactive decay to quantify the amount of activity present

### CHANCE

### Destructive analysis (DA)

Provides the most accurate and unbiased activity determination

- Involves sampling, sample preparation (dissolution/mineralization) chemical separation methods and radiometric measurements
- Sampling a critical step in the characterization process Designing the sampling procedures and checking the homogeneity and representativeness of the samples assures the reliability of the final results
- Radiometric determination is performed by instrumental analysis
  - LSC allow α-β spectrometry
  - α spectrometry
  - o high resolution γ spectrometry high and low energy γ emitters
  - mass spectrometry

### CHANCE

**CHANCE** outcomes on **RW** characterisation practices

### **CHANCE WP2 objectives**

- Collect end-users requirements in terms of characterization, especially links and overlaps between these requirements and waste specifications for different national disposals;
- Identify critical parameters to be measured for each waste type and their final disposal solutions and the commonly used evaluation techniques and problematic cases for radioactive waste package characterization;
- Identify R&D needs to develop and evaluate innovative technologies complementing current characterization techniques and providing supplementary

### CHANCE

### How to accomplish these objectives?

Based on a survey of characterization methodologies currently used by European waste generators, disposal operators and waste management organisations

A questionnaire was sent to CHANCE EUG members to identify:

- key parameters that need characterization;
- technologies/methods commonly used for characterization of conditioned RW;
- WAC applied and the possibilities of their harmonization in Europe
- specific problematic issues for the characterization of conditioned RW; R&D needs and potential on-going R&D programme on the topic of conditioned radioactive waste characterization;
- potential applications of R&D actions included in CHANCE;
- socio-technical and ethical issues associated with the waste characterization process.

# CHANCE Content of the questionnaire (1/2)

- 18 guestions related to the:
- RW, including SNF, managed by the EUG members
- The storage / disposal options
- The WAC for the storage / disposal facilities and the possibility of WAC harmonization across Europe
- Impact of the evolution of the WAC and of the final disposal concepts
- Methods applied in characterisation of conflictioned RW and the associated uncertainties (technical, conceptual, social, political, ethical) Waste categories and/or waste forms that do not have a dedicated option for storage / disposal
- The major difficulties characterisation of conditioned radioactive waste
- The R&D needs and on-going R&D programmes on characterisation conditioned RW
- Potential application of characterisation techniques improved in CHANCE Calorimetry, Muon Tomography and Cavity Ring-Down Spectroscopy

# CHANCE Content of the questionnaire (2/2)

- Characterisation and control processes: responsible organizations, structure ways to followed up these processes

  The role of host communities in the characterisation and control processes
- Disciplines / fields of expertise / actors involved in the characterization conditioned RW
- The importance of RW waste characterization
- Lessons learnt

### CHANCE Answers received

Nr.crt.	Country	Organisation	Туре
1	BE	ONDRAF/ NIRAS	WMC
2	ES	ENRESA	WMC
3	FR	ANDRA	WMC
4	,IT	Nucleco S.p.A.	WMC
5	PL	Radioactive Waste Management Plant	WMC
6	RO	ANDR	WMC
7	SE	SKB	WMC
8	UK	RWM	WMC
9	BE	SCK-CEN	RE
10	DE	JULICH	RE
11	FR	CEA	RE
12	PL	INCT	RE
13	RO	RATEN ICN	RE

### CHANCE

### Characterisation techniques used by CHANCE EUG members

- The methods used for RW characterisation depend on the country approach. The majority of the respondents to CHANCE questionnaire apply spectroscopic techniques (alpha, beta and gamma) as well as neutron measurements and dose rate calculation. Only few of them more advanced technique such as calorimetry.
- Nuclide vector and Scaling Factor methods are used by a large number of European countries, such as Belgium, France, Germany, Spain, Sweden, the UK.





### **RW** characterisation in Belgium

The characterisation process is based on the following techniques:

- gamma-spectrometry (for KN determination) combined with an approved nuclide vector (base on models, calculations, and sometime on destructive measurements);
- dose rate (measured on non-conditioned waste packages) conversion with approved NVs (nuclide inventor is calculated through specific conversion factors mSv/h to MBq determined using software such as MicroShield);
- destructive analysis and approved NV;
- · neutron measurements on conditioned waste;
- mass spectrometry, gamma spectrometry, alpha spectrometry...on samples of non-conditioned waste.

### CHANCE

### **RW** characterisation in France

The characterisation process is split into 2 phases:

- Determination of NVs and SFs for waste streams:
- Measure the waste itself: when a practical spectrum is known, it is needed
  to gain access to the waste activity. In this case, the aim is to measure one or more
  tracer(s) that can lead, with the knowledge of spectra, to the knowledge of every
  significant radionuclide by means of SFs and NVs. The measurement of this / those
  tracers is aimed to be easy and not hard-to-analyse.

Depending on the waste type, different methods are used :

- eperiumg on the waste type, different methods are used: y spectrometry on waste package; X-ray inspection; active neutron measurements for prompt or delayed neutrons; passive neutron measurements. DA: samples of waste package may also be collected (with destruction of the waste package), dissolved, then gamma spectrometry or radiochemistry are made.
- measurement of tritium degassing with LSC:

### CHANCE

### **RW** characterisation in Germany

### For operational waste:

- pre-characterization: source/origin of RW, radiological and material pre-sorting (mainly material stream separation and gamma activity / dose rate survey);
- (RCA), QA and ID/origin checks, temperature-range stability, outgassis control, temperature survey, dose rate at surface and 1m distance;
- measurement portfolio: dose rate/gamma spectroscopy, calorimetry,
- determination of heat, density, volume, mass, homogeneity, centre-of-mass
- sampling-statistics, random sampling for RCA;
- applied methods: AAS, ICP-MS, OCP-MS, gamma, neutron spectroscopy, QA-process control parameters, uncertainty assessment, LS/CRDS

### For decommissioning waste:

pre-characterization: source/origin of RW, radiological and material pre-sort (mainly material stream separation and gamma activity / dose rate survey);

### CHANCE

### RW characterisation in Italy

An integrated approach combining different methods, such as physical scanning, gamma spectrometry and neutron counting measurements.

- For the physical scanning an X-ray tube is used to analyse the matrix and its density distribution.
- The gamma spectrometry is performed by using HPGe detector and keeping the item (usually a drum with variable volume) in rotation to reduce the radial matrix effect.

- Open-geometry: one measure per waste package
   Segmented scarning: the waste package is be "cut" in segments (reconstructing the vertical distribution of both matrix and contamination)
   Tomography: a 3-dimensional reconstruction of matrix and contamination distributions.
- For the neutron counting measurements, a dedicated equipment able to detect neutrons coming from both spontaneous fissions (passive mode) and induced fissions (active mode) is used able to detect both fertile and fissile materials.

### CHANCE

### **RW** characterisation in Poland

To characterise the RW intended for storage, radiation activity measurements and eventually radiation spectroscopic measurements are made.

Usually, radioisotope composition of waste is determined on the basis of the end users' declaration.

Characterisation of the RW is simple, limited to the gamma dose rate in a single container sent for the treatment and disposal.

Each type of the waste is generally described: the volume, form of the waste, radionuclides present (according to the knowledge of the user) and time of generation.

### CHANCE

### **RW** characterisation in Romania

- For institutional waste sent for final disposal to National Repository Baita Bihor:
  - o gamma dose rate measurement

  - gamma spectrometry the activity of  $\alpha$  and  $\beta$  emitters is based on the measure carried out on row waste before conditioning or on the gene declaration.
  - Cernavoda NPP: no conditioned RW packages were produced up to date
  - C-14, H-3 and gamma emitters are measured on raw waste that ar regularly sent for incineration at an European operator
  - For the LLW, the process for developing scaling factors is on-going. The waste streams were identified and gamma measurements for ETD radionuclides were carried out. Also, the DTM radionuclides are measured on the identified waste streams by using adequate radiochemistry methods for their separation and purification and LSC and alpha spectrometry for quantification.

### **RW** characterisation in Spain

The ETM radionuclides are determined:

- by gamma dose rate measurement for waste with known gamma isotopic composition;
- segmented radiography for heterogeneous waste or for better improvement;
- by samples taken before the conditioning process for homogeneous waste, and further extrapolation as a function of the mass introduced; a final dose rate factor correction is applied if necessary,
- gamma spectrometry to the whole package/item;
- segmented /collimated gamma spectrometry heterogeneous waste or for better improvement.

The DTM radionuclides are assessed by using Scaling factors

### CHANCE

### **RW** characterisation in Sweden

The radiometric measurements are split in two categories:

- nuclide specific measurements of waste packages
- · non-package-specific data

The waste suppliers are requested to perform gamma spectrometry for each waste package disposed of in SFR (the final disposal for LILW-SL).

The activation product Co-60 and the fission product Cs-137 are considered "key nuclides" and are used in most of the calculation methods to determine the activity or distribute other DTM nuclides in the different waste vaults in SFR (final disposal facility for LILW-SL at Forsmark).

### CHANCE

### RW characterisation in the UK

Characterisation activities are undertaken by the waste producers, on raw waste, prior to any conditioning process.

Routine characterisation of row RW consists of radiological characterisation, routine sampling and analysis to confirm satisfactory operational processes, effluent characterisation, condition, monitoring and inspection (CMI) on inside existing storage facilities —based on British Standard inspection requirements.

Condition, monitoring and inspection techniques:

- Laser measurement of waste package geometry to detect waste container expansion
- Muon tomography was used in the past to support an understanding of the evolution of specific waste packages
- air sampling and discharge monitoring in storage facilities to confirm satisfactory operation
- Gas sample collection for selected packages

# CHANCE Difficulties in RW characterisation

(1/3)

- The proper characterization of the conditioned legacy/ historical waste packages represents a general problem, especially for countries with long-term utilization of nuclear technology (Be, De, Es, Fr, It, the UK).
  - cnnology (se, be, s., r., it, the UK).

    radiologic characterisation of these waste packages, especially in the case of large volume packages, represents a major challenge to either passive or active measurements because of the difficulty of the interrogators radiation to penetrate the waste matrix through strong attenuation before (gamma or neutron) emissions arrive at detectors placed around the waste package.
  - the type of different materials in historical waste is often difficult to identify
- Accelerator based waste for which the radionuclide vectors and material vectors were not defined yet and SNF for direct disposal are also considered categories of difficult to be characterized RW.

## CHANCE Difficulties in RW characterisation

- Determination of a viable source term in already conditioned RW a common problem mainly because the  $\alpha$  and  $\beta$  emitting radionuclides are DTM due to the the a and p emitting radionuclides are DTM due to the signal attenuation caused by the waste package itself and the backfill. These effects, in case of low or very low radioactivity or low energy emissions (such as the 59.54 keV gamma line for Am-24th), strongly compromises the measurement efficiency, leading to significant uncertainty of the measured activity.
- · Detection of declarable DTM isotopes (such as Sr-90) and sealed radioactive sources

### CHANCE Difficulties in RW characterisation

- Other identified problems in characterisation of conditioned RW consist of:
- little traceability of the chemical content of waste packages, when the conditioning is done by the waste producer;
- accessibility of the waste for sampling due to the limited access at the waste packages;

- access at the waste packages; difficulties in monitoring and periodical control of the waste drums packed deeply in a storage facility; characterization and reconditioning of the waste already stored in a repository the lack of standardized processes for the characterization and repackaging (or reconditioning) of spoilt drums/containers.

### How these problems could be solved?

By developing non-destructive methods capable to detect the radiological (including \alpha and \beta emitters) and fissile mass content with an acceptable uncertainty, compatible with the WAC for storage, transportation and final disposal.

These methods should be able to be applied for:

- homogeneous and heterogeneous waste
   waste packages of different sizes, including SNF casks.

### CHANCE

# EUG interest in applying techniques addressed by CHANCE

Calorimetry is seen as a useful technique in:

- diminution the uncertainty and/or detection limit for conditioned RW such as waste containing H-3 and Pu (in conjunction with other nuclear measurement techniques)
- to identify sealed spent sources or alpha/beta emitters with considerable heat load hidden in packages to be disposed of.
- Combined with gamma spectrometry, Calorimetry is considered to bring improvements to the currently used non-destructive techniques for DTM isotopes in conditioned waste packages.

CHANCE attempts to make the calorimetry applicable for large volume, heterogeneous and multi-nuclide waste packages

### CHANCE

### **EUG** interest in applying techniques addressed by CHANCE

Muon Tomography is regarded as a technique that:

- could replace the X-ray high energy for package with high
- stand-alone or combined with gamma imaging, Muon Tomography is considered useful to identify the: location and amount of high-Z

  - potentially fissile material in a waste package
  - position and integrity of SF-assemblies in very large storage casks
  - unwanted density depletion from voids or bubble formation in cemented drums
- Possibly useful for monitoring interim storage halls, maybe even filled and sealed repository galleries.

### CHANCE

### **EUG** interest in applying techniques addressed by CHANCE

Cavity Ring-Down Spectroscopy is considered very useful tool for:

- the extremely low limit outgassing monitoring of waste packages containing graphite waste exuding very small amounts of H-3 or C-14 or for the detection of Cl-36
- measuring in real time the emission of radioisotopes (in water vapour, CO<sub>2</sub>,...) In repositories and even in the reactor caissons, in case of graphite moderated reactors.

### CHANCE

### Conclusion

- The requirements for characterisation are driven by the WAC, either for storage or disposal facilities
- RW characterization is a very complex process that requires the use of in-situ measurements (NDA), sampling and analyses (DA) complemented with modeling and theoretical calculations.
- Process knowledge represents an important component of the characterization process
- Despite of various techniques already used in the RW characterisation process, there is need of developing new NDA methods capable to detect the radiological (including  $\alpha$  and  $\beta$  emitters) and fissile mass content with an acceptable uncertainty, compatible with the WAC for storage, transportation and final disposal





### Questions?



































































### 5. Challenges ahead

- Approach for waste produced before disposal criteria: pre-disposal control by random checks
   Study goes on
   Emphasis added on physical and chemical content!
- Necessity of an approach for historical waste with poor characterization: case by case
- Management of uncertainties in characterization
- Reconditioning of non-compliant waste?
   Eg. thermal treatment will destroy all organic compounds
   Characterization remains necessary!




































































































Calorimetry

\* Calorimetry is a technique for measuring the thermal power produced by the nuclear decay of any radioactive material


It is a non destructive assay used mainly for tritium, plutonium and americium quantification based on the knowledge of the isotopy.


The item to be studied is placed in the calorimeter measurement chamber and the heat flow at equilibrium, that is, the thermal power, from the item is determined by temperature sensors and associated electronic equipment


The thermal power emitted by a test item is directly related to the quantity of the radioactive material in it





\* In calorimeters designed for the characterisation of large samples (>100 U,) the implementation of a ghost reference cell placed below the measurement sample and with the same thermal capacity is favourable.




























Experimental investigation


Experimental investigation with LVC CHANCE will measure plutonium and other possibly hidden RN in realistic cases with 200L mock-up waste drums and real unconditioned waste drum at CEA Caderache and SCK.CEN





# A SCK-CEN, the experimental program will consist of maximum six configurations with well-defined matrix and radiological content (PuO<sub>2</sub> pins). In order of priority: A neal unconditioned waste drum. Effect of matrix: "Homogeneous" source distribution inside > A new morar mock-up with ethafoam > An existing mock-up with ethafoam, PVC and steel Effect of neterogeneity. The new mortar mock-up with > The largest-activity source in the center > The largest-activity source at the border
























# Existing calorimeters: Measurement of drums from 3,3 to 380 liters Easy to use Power range: from 100 µW to 100 W (from few mg to tens grams of tribum and from grams to kilograms of Pu) Calorimetry measures the radioactive heat flux Calorimetry measures all heat emitted from the drum and deposited inside the calorimetry measures all heat emitted from the drum and deposited inside the calorimetry arrivals. Ant miss any heat emission / deposition (above detection limit and except escaping particles) New target for calorimetry is to focus on multi-radionuclide compounds for instance in bituminous and cemented waste drums with quite hydrogenous matrix material. Numerical modelling makes possible to properly analyze the data and therefore reduces the detection limits and better quantifies the uncertainties.

Conclusion and Outlook


CHANCE














































# Conclusions Presently, Safeguards inspectorates face challenges due to increased amounts of spent fuel in EU MS. No feasible traditional NDA technique could be used for verification of NM in dry storage casks. Some novel technologies can be potentially used for verification purposes. Muography is a source-free technique, which is well advanced. Simulations and field tests show high potential of muography for dry storage cask verifications The content and configuration of SF in dry cask is supposed to be well known initially – thus one looks for any deviations from known configurations












































































































































































































































































































































































## References

- Joint Committee for Guides in Metrology. (2008). Evaluation of measurement data: Guide to the expression of uncertainty in measurement. (20 pp. http://www.nov.org/niter/ECMM/CMM-Introduction/time. International Organization for Standardzaulor, (2010), 190-11929. Determination of international Organization for Standardzaulor, (2010), 190-11929. Determination of confidence interval for measurements of inoxing radiation. Fundamentals and application, https://www.inco.org/niter/acm/18181.html.

  Joint Committee for Guides in Metrology. (2008). Evaluation of ressurement data. Supplement 1 to the figure to the expression of uncertainty in measurement data. Supplement 1 to the figure to the expression of uncertainty in measurement. Kinghatrick, J.M., Verkitations, J.M., Verkitation, B.M. (2018). Minimum detectable activity, systematic uncertainties, and the ISO 11929 standard. Journal of Radioansylation and Nutzber-Chemistry, 2605, 1005–1010.

  Standard Standard Standard Standard Standard Measurement equipment used in release processed during decormissioning, 10th International Symposium Referse or Radioansylation Measurement equipment used in release processed during decormissioning, 10th International Symposium Referse or Radioansylation Measurement equipment used in release processed during decormissioning, 10th International Symposium Referse or Radioansylation Measurement equipment used in release processed during decormissioning, 10th International Symposium Referse or Radioansylation Measurement equipment used in release processed during decormissioning, 10th International Symposium Referse or Radioansylation Measurement equipment used in release processed during decormissioning, 10th International Symposium Referse or Radioansylation Measurement equipment used in release processed during decormissioning, 10th International Symposium Referse or Radioansylation Measurement equipment used in release processed during decormissioning, 10th International Symposium Referse or Radioansylation Measurement equipment u

## Copyright © 2018 - SCX\*CEN

All properly rights and copyright are enerved.
Any communication or reproduction of this document, and any communication or use of its content without explicit authorization by the content without explicit authorization is primated as by efficiencement to this rule is linguis and entitles to claim damages from the inferiogic without of granting is patient or registration in the field of intellectual property.

SCINCEN
Studiecenfrum voor Kernenergie
Centre di Ebude de l'Ebergie Nucléaire
Belgian Nuclear Research Centre

Sichting van Openbaar Nut-Fondation of Utilité Publique Foundation of Public Utility

Registered Office: Avenue Hermann-Debrouxlain 40 = 8E-1160 BRUSSEL Operational Office: Boeretang 200 = 8E-2400 MOs.